



LCC

BIOMETRIC COMBO DEVICE



Product Description

LCC is a cost competitive combo to acquire fingerprints on the go and it encapsulates an Android device with a high resolution camera and a separate fingerprint reader in a rugged cover. It is aimed at the market of client’s registration where there is a requirement of biometrics and picture of the client.

LCC is a cost effective product combining a device with camera and a versatile fingerprint reader in a rugged case. LCC is the perfect solution for wide spread registration of clients.

For more information please visit: www.biorugged.com



HIGHLIGHTS

- Android Terminal with 4.5-5” Screen*
- High Resolution Camera*
- USB Fingerprint Reader*
- Communications: 3G, LTE, Bluetooth and Wi-Fi*
- Rugged Case*
- Large and Long Life Battery (Full work day operation)*
- KYC Device designed to meet all local government regulation*
- Protective Rubber/Leather cover*
- Endless branding opportunities (color, logos and images)*

About BioRugged

BioRugged is a fast growing company delivering solutions to an increasingly demanding global market of specialized devices. Our expertise resides in creating rugged printing, biometric and POS devices or any combination of these technologies for a wide range of applications. Governments, logistics companies, mobile operators, healthcare organizations and military are just a few of end-users for BioRugged terminals.

For more details please visit: www.biorugged.com

BIOMETRIC COMBO DEVICE

SPECIFICATIONS



5 Megapixel Camera

Processor	MT6735P
Operating System	Android 4.4
Internal Memory	1GB RAM, 8GB FLASH, Ext. TF microSD, up to 32GB
Communications	GSM/WCDMA/4G



Rugged Case

Display	HD 5.0' IPS, Capacitive TP
SIM	Dual sim cards dual standby
Back Camera	8Megapixel, High Definiton
Front Camera	2Megapixel
Data	GPRS/EDGE/3G/WLAN/Bluetooth/USB



Fingerprint Scanner

Battery	Li-ion 4000mAh
Dimensions	145.5*75.5*9.3mm
Weight	200g
Protection Class	IP65, waterproof, dustproof, crashproof
Fingerprint	Built-in Fingerprint Module, 320 x 480 pixel ANSI-378, ISO19794-2, ISO19794-4, WSQ